

care and cleaning

The fine “furniture” finish of Diamond cabinets is designed to withstand hard usage. All wood and laminate surfaces may be cleaned with a soft cloth moistened with pure soap suds (not detergent) then wiped dry with another soft cloth.

Once or twice a year, after cleaning, a light coat of self-cleaning wax may be applied to laminate surfaces for added protection. For wood surfaces, a light coat of furniture polish is

recommended. Take extra care on the bottom edge of base cabinets and base cabinet doors where moisture often collects.

Do not use detergents, soap pads, steel wool or other harsh abrasive material on your Diamond cabinets.

For complete guidelines refer to Diamond’s website, www.diamond-cabinets.com for Diamond’s Care.

trouble shooting

As a do-it-yourselfer, you have assumed the role of the contractor. In assuming this role, there are certain responsibilities that could become necessary to “finish” the job once installed.

CONDITION	POSSIBLE CAUSE	REMEDY
Double doors on cabinet or base do not line up.	1. Cabinet not set level and square (plumb) or cabinet is in a twist (racked).	1. Loosen screws in wall and use shims to make cabinet plumb. 2. Loosen hinge* screws on cabinet frame and adjust alignment. Re-tighten screws to frame.
Door is not flush with cabinet face frame at either top or bottom.	1. Hinge twisted. Cabinet racked. 2. Door warped due to insufficient humidity.	1. Make sure cabinet is plumb and level. Then, adjust hinge*. 2. Refer to warped door policy on previous page.
Drawer face does not fit flush with cabinet.	1. Drawer guide out of alignment.	1. Before counter tops are installed, adjust the guide by sliding it right or left in the back bracket. Guides must be parallel.

*See Step 9-Door and Drawer Alignment for details



Diamond cabinets meet or exceed the strict recommended performance and construction standards set forth by the Kitchen Cabinet Manufacturers’ Association.

